

 1 Cranfield Rd. Lostock, Bolton, BL6 4SB Tick Box(s) As required		BAY WINDOW ORDER FORM Heritage Customer Name & Address:		Delivery Address if different: Contact Name: Contact Number:		Customer Reference Customer Order Number Date Required Total Payable <u>Excluding</u> VAT £	
FRAME COLOUR External Internal		HANDLE COLOURS Windows Doors		DOUBLE GLAZED UNGLAZED SUPPLY PANELS		FLUSH CASEMENT (Tick if required) (Standard casement will be supplied unless ticked) Not available on Doors or Tilt & Turns	
70mm Large Outer frame (Standard Outer Frame is 60mm—White only)		Fit dog bolts (windows & doors)		Enhanced Security PAS 24 OR PAS 24 & SBD		Secured By Design [SBD] Please provide detail on each bay below, i.e. Laminated glazing, non-lock handles etc.	
BAY 1 Sketch each bay below (Viewed from outside) (tick box(s) as req) SUPPLY 20mm 35mm 50mm Frame Add Ons to top of all frames SUPPLY a 20mm 35mm 50mm Add On to L/H Side Frame SUPPLY a 20mm 35mm 50mm Add On to R/H Side Frame						Overall Height inc. any cill Sash Width: Transom Drop: Cill Type: 150 85 180 None FACE Drain OPTIONAL BAY POLE REQUIREMENTS (Standard Pole/Posts supplied) Load Bearing 9mm Coupler Suitable for Bows only between 160° - 180° Show on sketch HINGE TYPES Egress Fire escape Tristay Restricted, Fire escape Restricted Hinge Cavity Restrictor HANDLES Non Lock Handles Trickle Vents (Show on Sketch) 4000 or 5000 Sash or Frame	
BAY CILL PLAN—EXTERNAL VIEW To Avoid Delays please provide as much information as possible including internal angles, internal back of cill sizes, projections etc... Location				GLASS /PAN. DETAILS Black Warm Edge Bar & Argon gas to all units as standard (clear soft coat unless specified) Glass Specification Toughened/ Obscure Geo Bar, Etc. Enlighten™ Triple Circle as req. 28mm 36mm Other Notes:			
BAY 2 Sketch each bay below (Viewed from outside) (tick box(s) as req) SUPPLY 20mm 35mm 50mm Frame Add Ons to top of all frames SUPPLY a 20mm 35mm 50mm Add On to L/H Side Frame SUPPLY a 20mm 35mm 50mm Add On to R/H Side Frame						Overall Height inc. any cill or Frame Exten. Sash Width: Transom Drop: Cill Type: 150 85 180 None FACE Drain OPTIONAL BAY POLE REQUIREMENTS (Standard Pole/Posts supplied) Load Bearing 9mm Coupler Suitable for Bows only between 160° - 180° Show on sketch HINGE TYPES Egress Fire escape Tristay Restricted, Fire escape Restricted Hinge Cavity Restrictor HANDLES Non Lock Handles Trickle Vents (Show on Sketch) 4000 or 5000 Sash or Frame	
BAY CILL PLAN—EXTERNAL VIEW To Avoid Delays please provide as much information as possible including internal angles, internal back of cill sizes, projections etc... Location				GLASS /PAN. DETAILS Black Warm Edge Bar & Argon gas to all units as standard (clear soft coat unless specified) Glass Specification Toughened/ Obscure Geo Bar, Etc. Enlighten™ Triple Circle as req. 28mm 36mm Other Notes:			
 Please accept my order as detailed. All orders supplied in accordance with our current Terms & Conditions. IMPORTANT NOTE: Only WRITTEN notification of any CANCELLATIONS / ALTERATIONS to this ORDER will be considered. Cancellation / Alteration costs may be incurred. Signed Date:Pageof It is the responsibility of the person ordering to ensure all designs and specification comply with all current legislation. ie. Building Regulations Doc B, F, L, N etc. Advice is available on request							
orders@heritagetradeframes.co.uk Phone: 01204 664700 ref: Bay Wind OF Jan24							